

NLED49*

IP protected surface mounted fixture



SPECIFICATION


- Up to 50% energy saving compare with
- Long lifetime, up to 30000 hours
- High efficiency SMD LED chips 100lm/W τ 8
- High power factor LED constant current driver
- PC diffuser, stainless steel clips
- Easy maintenance, serviceable design

APPLICATIONS


- Parking garages, industrial halls, storage facilities

PHOTOMETRIC DATA

NLED491 18W



NLED492 36W



Model	a	b	L
NLED491 18W	110mm	85 mm	650 mm
NLED492 36W	110mm	85 mm	1265 mm
NLED493 54W	110mm	85 mm	1550 mm

Model	Watt	Lumen	Lumen/Watt	Color temp.	CRI
NLED 491 18 W 3000K	18 W	1800 lm	100 lm/W	3000 K	80
NLED 491 18 W 4000K	18 W	1800 lm	100 lm/W	4000 K	80
NLED 492 36 W 3000K	36 W	3600 lm	100 lm/W	3000 K	80
NLED 492 36 W 4000K	36 W	3600 lm	100 lm/W	4000 K	80
NLED 493 54 W 3000K	54 W	5400 lm	100 lm/W	3000 K	80
NLED 493 54 W 4000K	54 W	5400 lm	100 lm/W	4000 K	80