



LED panel CAPRI SLIM 600x600mm

2 YEARS WARRANTY



Model	Power	Lumens	Kelvin	CRI	Beam Angle	Input	Dimensions (mm)
2R LED panel CAPRI SLIM 600X600X8 40W	40 W	3600	3000 K	>80	120°	AC 230V	595x595x9
2R LED panel CAPRI SLIM 600X600X8 40W	40 W	3600	4000 K	>80	120°	AC 230V	595x595x9
2R LED panel CAPRI SLIM 600X600X8 40W	40 W	3600	6500 K	>80	120°	AC 230V	595x595x9
2R LED panel CAPRI SLIM 600X600X9 48W	48 W	4800	3000 K	>80	120°	AC 230V	595x595x9
2R LED panel CAPRI SLIM 600X600X9 48W	48 W	4800	4000 K	>80	120°	AC 230V	595x595x9
2R LED panel CAPRI SLIM 600X600X9 48W	48 W	4800	6500 K	>80	120°	AC 230V	595x595x9



LED panel CAPRI SLIM 600x600mm Dimmable

2 YEARS WARRANTY



Model	Power	Lumens	Kelvin	CRI	Beam Angle	Input	Dimensions (mm)
2R LED panel CAPRI SLIM DIMM 600X600X8 40W	40 W	3600	4000 K	≥80	120°	AC 230V	595x595x9
2R LED panel CAPRI SLIM DIMM 600X600X8 48W	48 W	4800	3000 K	>80	120°	AC 230V	595x595x9
2R LED panel CAPRI SLIM DIMM 600X600X8 48W	48 W	4800	4000 K	>80	120°	AC 230V	595x595x9
2R LED panel CAPRI SLIM DIMM 600X600X8 48W	48 W	4800	6500 K	>80	120°	AC 230V	595x595x9



LED panel FAIRY SLIM

UGR<19

Микропризматичен разсейвател ограничаващ заслепяването

3 YEARS WARRANTY



Model	Power	Lumens	Kelvin	CRI	Beam Angle	Input	Dimensions (mm)
2R LED panel FAIRY SLIM 600X600X9 40W UGR<19	40 W	4000	4000 K	≥80	120°	AC 230V	595x595x9
2R Frame OM 600x600x55 mm Metal							613x613x58
2R Frame OM 600x600x45 mm Aluminium							605x605x50
2R Hanging set							
2R LED Emergency unit							