

LED Downlight WAVE 3-white























	Model	Power	Lumens	Kelvin	CRI	Beam Angle	Input	Dimensions (mm)	Cut Out (mm)		
2R	LED Downlight WAVE R70 7W 3-white	7 W	660/700/700	3000/4000/6000	>80	90°	AC230V	Ø95x58	Ø68-80		
2R	LED Downlight WAVE R92 10W 3-white	10 W	950/1000/1000	3000/4000/6000	>80	90°	AC230V	Ø113x59	Ø90-102		
2R	LED Downlight WAVE R130 14W 3-white	14 W	1330/1400/1400	3000/4000/6000	>80	90°	AC 230V	Ø145x66	Ø120-130		
2R	LED Downlight WAVE R150 17W 3-white	17 W	1600/1700/1700	3000/4000/6000	>80	90°	AC230V	Ø174x69	Ø145-155		
2R	LED Downlight WAVE R205 25W 3-white	25 W	2400/2500/2500	3000/4000/6000	>80	90°	AC230V	Ø244x85	Ø195-210		



2R LED Downlight WAVE R150 17W DIMM 3-white Ø174x69 Ø145-155 17 W 0-10V 3000/4000/6000 >80 AC230V 2R LED Downlight WAVE R205 25W DIMM 3-white 25 W AC 230V Ø195-210 0-10V 3000/4000/6000 >80 Ø244x85



Cover INOX for WAVE

	Model	Dimensions (mm)	
2R	Cover INOX for WAVE R92 10W	Ø113	
2R	Cover INOX for WAVE R150 17W	Ø174	
2R	Cover INOX for WAVE R205 25W	Ø244	