

E Plus Super Pro SMD

130 Lm/W




Classification _____

| | | | |
|------------|------------|-------------------|--------------------|
| 50000 hrs | A++ | IP65 | Beam Angle 120° |
| CRI ≥80 | PF >0.9 | Voltage AC230V | Body Type PC/PC |

BOX
1 pcs


Dimensions _____



Dimming Option 0-10V _____



Photometric Data



| SKU | Model | EQ. Watts | Lumens | Kelvin | AxBxC mm |
|-------|----------------------|-----------|--------|--------|-------------|
| 83431 | E Plus Super Pro SMD | 20W | 2600 | 4000K | 600x104x80 |
| 83455 | E Plus Super Pro SMD | 20W | 2600 | 6000K | 600x104x80 |
| 83479 | E Plus Super Pro SMD | 40W | 5200 | 4000K | 1200x104x80 |
| 83493 | E Plus Super Pro SMD | 40W | 5200 | 6000K | 1200x104x80 |
| 83516 | E Plus Super Pro SMD | 60W | 7800 | 4000K | 1500x104x80 |
| 83530 | E Plus Super Pro SMD | 60W | 7800 | 6000K | 1500x104x80 |
| 83554 | E Plus Super Pro SMD | 75W | 9750 | 4000K | 1500x104x80 |
| 83578 | E Plus Super Pro SMD | 75W | 9750 | 6000K | 1500x104x80 |
| 86876 | LED Emergency unit | | | | |